

# **iSpeaker AAC4**

40W Ceiling Speaker

*Datasheet V1.1*





# Table of Contents

- 1. INTRODUCTION ..... 3
- 2. FEATURES ..... 3
- 3. PACKAGE CONTENTS ..... 3
- 4. SPECIFICATION ..... 4
- 5. CONNECTION..... 5
- 6. PRODUCT DIMENSION ..... 5

# 1. INTRODUCTION


The iSpeaker AAC4 is the representative of the new technical in-ceiling speakers. It gives you the excellent sound effects and is suitable for background music and calling system. It is the best choice for the business places that need wide band, including hotels, restaurants, clubs and conference.

6.5-inch semi-automatic installation without rear barrel, constant pressure, constant resistance, adjustable high-fidelity ceiling speaker.

# 2. FEATURES

- 6.5-inch semi-automatic
- High Voltage and Constant Impedance
- Tweeter: 1" rotatable silk soft dome
- Woofer: 6.5" polypropylene cone
- Sensitivity: 90dB@1W/1m
- Rated power (8Ω): 40W
- Rated power (70V): 40W/20W/10W/5W
- Rated power (100V): 40W/20W/10W
- Frequency Response: 57Hz-20KHz
- Dimensions: 229×101mm
- Depth: 98.3mm


# 3. PACKAGE CONTENTS



**iSpeaker AAC4: 1pcs**



**Mesh Cover: 1pcs**



**Cutout Template: 1pcs**

## 4. SPECIFICATION

Model	iSpeaker AAC4
Name	40W Ceiling Speaker
Tweeter	1" rotatable silk soft dome
Woofers	6.5" polypropylene cone
Sensitivity	90dB@1W/1m
Frequency response	57Hz-20kHz
Rated power (8Ω)	40W
Rated power (70V)	40W/20W/10W/5W
Rated power (100V)	40W/20W/10W
Dimensions	229×101mm
Depth	98.3mm
Total height of speaker	108mm
Installation Thickness	15-37mm
Drill Diameter	201-220mm
Outer Diameter	231mm
Operating Temperature	- 10°C~+50°C
Storage Temperature	- 20°C~+60°C
Humidity	90% (non-condensing)
Net Weight (Each)	1.8KG
Gross Weight	13.9kg (6pcs in one CTN)
Package Dimension	559*445*290mm (6pcs in one CTN)

## 5. CONNECTION

Connect the two push-down binding ports to the amplifier output.



## 6. PRODUCT DIMENSION

